

SL1838BC

BUTTON CAP STAPLER 38MM MAX

SL

Diameter: 0.9 - 1.3mm
Crown: 8 - 8mm
Length: 19 - 38mm

SB-CAPS

Diameter: 25 - 25mm
Crown: 25 - 25mm





Features

Mg

Magnesium Housing

Hand icon

Rubber Comfort Grip

Anti Slip Bumpers

Anti Slip Bumpers

Oil Free Engine

Oil Free Engine

Rear Exhaust

Rear Exhaust

SPECIFICATION				
Power type		Pneumatic		Operating pressure
Weight		1.77 kg		4.80 - 8.30 BAR
Width		159 mm		70.00 - 120.00 PSI
Length		286 mm		Air Consumption Ltr.per shot @ 5.6 bar
Height		267 mm		1.33
Magazine capacity (max)		100		Air fitting thread type
SL Series Fasteners:				1/4 BSP
Diameter (mm)		0.9 (min)	1.3 (max)	Noise
Crown (mm)		8 (min)	8 (max)	LPA 1sd
Length (mm)		19 (min)	38 (max)	86.59
SB-CAPS Series Fasteners:				LWA 1sd
Diameter (mm)		25 (min)	25 (max)	94.16
Crown (mm)		25 (min)	25 (max)	LPA 1s, 1m
				81.20
				Vibration / Uncertainty
				2.944 / 1.472 m/s2